



MOTO 2T SYNTECH



Description

Synthetic 2T lubricant which improves response against wear and high power combustion. Reduce the amount of visible smoke and deposit formation.

- Can be used on motorbikes with separate lubrication or manual system.
- Compatible with catalytic converters.
- For all scooter used in urban environments.
- Quickly mix with all types of commercial fuel.

Use

To mix: recommended between 2% and 4% (50: 1 to 25: 1) or (1.6 to 3.3 OzxGL) according to manufacturers' recommendations and adapted to the regime of use.

Technical data

Characteristics	Standard	Typical
Color		Red
Density 15° C	ASTM D 4052	0,868
Viscosity 100° C	ASTM D 445	7.5
Viscosity 40° C	ASTM D 445	48
Viscosity index	ASTM D 2270	120 mín
Flash point open cup	ASTM D 92	70 mín
Pour point	ASTM D 97	-18

Quality level

- API TC
- JASO FC (Nº 039PLE202) JASO M 345
- ISO-L-EGD
- TISI

Rev: 160803



EXCELENCIA PARA SU MOTOR



POL. IND. EL CAMPILLO, C/ ALEMANIA, 5/N
50.800 ZUERA - ZARAGOZA



+34 976 681 309
+34 902 430 540



WWW.MTLUBRICANTES.COM



INFO@MTLUBRICANTES.COM